

Apollo AL-924/AF-924

Compact 4 Line Alphanumeric Pagers



Features:

- Compact pager with 4 line display for 84 Alpha characters.
- Total capacity: 8150 characters memory for POCSAG.
- Button programmable..
- 6 Capcode capacity which can be personal or maildrop with no frame restrictions.
- Time, date display
 - International date format dd-mm-yy
- 16 sets of memory, eight lockable
- Four alert modes:
 - Beep
 - Vibrator
 - Melody
 - Sleep
- Ten melodies, four beeper sounds
- LCD backlight for easy viewing
- Alarm function
- Low Battery indicator and alarm
- Suitable for Network or Local Area Paging.
- 12 Month service warranty

A compact hand programmable 4 line alphanumeric pager with zoom function (zooms display to 2 lines large characters) and synthesised receiver (pocsag).

Specifications

- | | |
|-----------------------|---|
| • Protocols | Pocsag (AL924)
Flex (AF924) |
| • Frequencies: | 132–174 MHz
443–473 MHz |
| • Frequency Set | Synthesised (AL924)
Crystalled (AF924) |
| • Baud rate: | 512, 1200 or 2400bps |
| • Sensitivity | 512 BPS--5uV/M
1200 BPS--7uV/M |
| • Spurious Rejection | 40db below carrier |
| • Channel Spacing | 25 kHz |
| • Selectivity | 60db @ 25 kHz |
| • Alert Tone Loudness | 85db @ 30 cm |
| • Frequency deviation | +4.5 kHz |
| • Cap codes | 6 Cap Codes (AL924) |
| • Dimensions | 61 x 42 x 18 mm |
| • Battery | One 1.5 V AAA Alkaline |

AL901/AF901 Numeric Pager



Top display synthesised (AL901) numeric pager available in VHF and UHF. Button programmable.